



REVISIONS		DESCRIPTION	DRAWN	CHECKED	APPROVED
REV	DATE				
		Capacity(용량)	tf	100	
		Rated Output(정격 출력)	mV/V	2.0±0.002	
		Zero Balance(무부하 범위)	mV/V	0.0±0.02	
		Combined Error(종합 오차)	%RO	0.1	
		Repeatability(반복 출력 허용)	%RO	0.05	
		Creep for (30min)N분출력편차	%RO	0.1	
		Temperature effect on(온도변화에 따른 범위)			
		Zero Value(영점값)	%RO/10°C	0.03	
		Output Value(출력값)	%RO/10°C	0.03	
		Excitation(인가전압)			
		Recommended(권고 전압)	V	10	
		Maximum(최대 전압)	V	15	
		Resistance(저항)			
		Input(입력저항)	Ω	760±60	
		Output(출력저항)	Ω	700±7	
		Insulation(절연저항)	MΩ	>2000	
		Compensated Temp.Range	°C	50 ~ +150	
		Operating Temp.Range(작동범위)	°C	20 ~ +180	

NO	TITLE	MATERIAL	Q'TY	REMARKS		
	TOLERANCES UNLESS OTHERWISE SPECIFIED	NAME OR TITLE CHCP-100TH SPEC				
	ANGULAR ± 0.1	CURIOSITY TECHNOLOGY CURIOTEC. CO. LTD 581-1, Yongmi-ri, Goangtan-myeon, Palu-si, Gyeonggi-do, South KOREA, 413-855				
	DECIMAL ± 0.1	FIRST USED IN ASSEMBLY	MATERIAL	paint finished steel		
	Q'TY/BET	FIRST MADE FOR	END FINISH			
		CONTRACT OR CUSTOMER NO	DIMENSIONS ARE IN (MM), INCH			
DRAWN	CHECKED 1	CHECKED 2	APPROVED	SCALE	DRAWING.PART NO.	REV
HB.S				N/S	CHCP-100TH -SPEC	0
2019.07.26						