



| REVISIONS | | 6 | 7 | 8 | |
|-----------|------|------------------------------------|----------|--------------|----------|
| REV | DATE | DESCRIPTION | DRAWN | CHECKED | APPROVED |
| | | Capacity(용량) | tf | 10 | |
| | | Rated Output(정격 출력) | mV/V | 2.0±0.0002 | |
| | | Zero Balance(무부하 범위) | mV/V | 0.0±0.05 | |
| | | Combined Error(종합 오차) | %RO | 0.05 | |
| | | Repeatability(반복 출력 허용) | %RO | 0.03 | |
| | | Creep for (30min)N분출력편차 | %RO | 0.04 | |
| | | Temperature effect on(온도변화에 따른 범위) | | | |
| | | Zero Value(영점값) | %RO/10°C | 0.05 | |
| | | Output Value(출력값) | %RO/10°C | 0.05 | |
| | | Excitation(인가전압) | | | |
| | | Recommended(권고 전압) | V | 10 | |
| | | Maximum(최대 전압) | V | 15 | |
| | | Resistance(저항) | | | |
| | | Input(입력저항) | Ω | 350±3.5 | |
| | | Output(출력저항) | Ω | 350±3.5 | |
| | | Insulation(절연저항) | MΩ | >2000@50V DC | |
| | | Compensated Temp.Range | °C | 40 ~ +150 | |
| | | Operating Temp.Range(작동범위) | °C | 20 ~ +180 | |

Cable Color Code
 Ex+ ▷ Red
 Ex- ▷ White
 Sig+ ▷ Green
 Sig- ▷ Blue
 Shield
 CABLE : SILICON Ø5-10m

| NO | TITLE | MATERIAL | Q'TY | REMARKS | | | |
|----|---------------------------------------|-------------------------|------------------------------|---|-------|------------------|-----|
| | TOLERANCES UNLESS OTHERWISE SPECIFIED | NAME OR TITLE | | CURIOSITY TECHNOLOGY CURIOTECH. CO. LTD 581-1, Yongmi-ri, Goangtan-myeon, Paju-si, Gyeonggi-do, South KOREA, 413-855 | | | |
| | ANGULAR ± 0.1 | CMNP-10TH SPECIFICATION | | | | | |
| | DECIMAL ± 0.1 | FIRST USED IN ASSEMBLY | MATERIAL | Stainless Steel | | | |
| | Q'TY/SET | FIRST MADE FOR | END FINISH | | | | |
| | | CONTRACT OR CUSTOMER NO | DIMENSIONS ARE IN (MM), INCH | | | | |
| | DRAWN | CHECKED 1 | CHECKED 2 | APPROVED | SCALE | DRAWING.PART NO. | REV |
| | K.A.H | | | | N/S | CMNP-10TH -SPEC | 0 |
| | 2019.06.10 | | | | | | |